

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

WHAT IS CLAIMED IS:

1. A monitoring apparatus comprising:

a gas sampling unit for sampling flue gas or atmospheric air;

5 an ion source for ionizing components present in very small amounts in said flue gas or atmospheric air under atmospheric pressure or a pressure based thereon;

a mass analyzing unit, provided in a region evacuated to a pressure lower than atmospheric, for mass analysis of ions
10 generated by said ion source and measuring their ion current signals; and

a data processor for processing the measured signals;

wherein at least one of dioxins, chlorobenzenes and chlorophenols in said flue gas or atmospheric air is monitored.

15 2. A monitoring apparatus according to claim 1, wherein said ion source is an atmospheric pressure chemical ion source operating in a negative ion mode.

3. A monitoring apparatus according to claim 2, wherein said analyzing part is an ion trap mass analyzing part.

20 4. A monitoring apparatus according to claim 3, wherein said monitoring is performed by integrating ion currents derived from isomers of dioxins, chlorobenzenes or chlorophenols.

5. A monitoring apparatus according to claim 4, wherein said monitored ion species of dioxins, chlorobenzenes or
25 chlorophenols comprises ions based on stable isotopes of the

chlorine atom.

6. A monitoring apparatus according to claim 3, wherein said monitored ion species are ions wherein a chlorine atom has been removed from M^- , $(M-Cl+O)^-$ or orthoquinone ions in the case of dioxins, M^- or $(M-Cl)^-$ in the case of chlorobenzenes, and M^- or $(M-H)^-$ in the case of chlorophenols.

7. A monitoring apparatus comprising:

a gas sampling system for sampling flue gas or atmospheric air;

an ion source for ionizing component present in very small amounts in said flue gas or atmospheric air under atmospheric pressure or a pressure based thereon;

a mass analyzing part, provided in a region evacuated to a pressure lower than atmospheric, for mass analysis of ions generated by said ion source and measuring their ion current signals; and

a data processor for processing measured signals;

wherein at least one organic or inorganic compound containing at least one element from Group VI or Group VII of the periodic table such as oxygen, sulfur or halogen in the molecule of said component, is monitored.

8. A monitoring apparatus according to claim 7, wherein said organic compound is at least one of dioxins, chlorobenzenes or chlorophenols.

9. A monitoring apparatus according to claim 8, wherein

said inorganic compound is at least one of nitrogen oxides (NO_x), sulfur oxides (SO_x), hydrogen chloride (HCl), chlorine (Cl_2) or oxygen (O_2).

10. A monitoring apparatus according to claim 9, wherein
5 the measurement of said inorganic compound and the measurement of said organic compound are performed separately on a time sharing basis.

11. An incinerator, wherein a sample gas is directly
introduced to an atmospheric pressure ion source via a pipe,
10 and at least one component of dioxins, chlorobenzenes or chlorophenols is monitored by ionizing components present in very small amounts in said sample gas and performing mass analysis.

12. A method of monitoring chemical substances comprising
15 the steps of:

sampling a gas containing hydrocarbons;

separating a sample gas from said gas, a first
introducing step for introducing said separated sample gas to
an ionizing unit;

20 ionizing and producing ionized substances by
subjecting said introduced sample gas to a discharge, a second
introducing step for introducing said ionized substances to an
ion trap analyzing part; and

detecting an ion current of predetermined ionized
25 substances.

13. A method of monitoring chemical substances comprising the steps of:

sampling a gas containing hydrocarbons;

5 separating a sample gas from said gas, a first introducing step for introducing said separated sample gas to an ionizing unit;

ionizing and producing ionized substances by subjecting said introduced sample gas to a discharge, a second introducing step for introducing said ionized substances to an ion trap analyzing part; and

10 detecting a mass of predetermined ionized substances.

14. A method of monitoring chemical substances according to Claim 12 or 13, wherein an ion trap mass spectrometer is used as said ion trap analyzing part.

15 15. A method of monitoring chemical substances comprising the steps of:

sampling a gas comprising hydrocarbons;

20 separating a sample gas from said gas, a first introducing step for introducing said separated sample gas to an ionizing unit;

ionizing and producing ionized substances by subjecting said introduced sample gas to a discharge, a second introducing step for introducing said ionized substances to an ion trap mass analyzing part;

25 producing ion substances wherein an atom is removed

from the ionized substances introduced in said second
introducing step; and

detecting an ion current of said ion substances.

16. A method of monitoring chemical substances comprising
5 the steps of:

sampling a gas comprising hydrocarbons;

separating a sample gas from said gas, a first
introducing step for introducing said separated sample gas to
an ionizing unit;

10 ionizing and producing ionized substances by
subjecting said introduced sample gas to a discharge, a second
introducing step for introducing said ionized substances to an
ion trap mass analyzing part;

15 producing ion substances wherein either an atom or
molecule has been removed from the ionized substances introduced
in said second introducing step; and

detecting an ion mass of said ion substances.

17. A method of monitoring chemical substances comprising
the steps of:

20 producing ion substances wherein a hydrogen atom has
been removed from dioxin precursors in flue gas;

introducing said ion substances to an ion trap mass
spectrometer;

25 producing negative ions wherein a chlorine atom of the
dioxin precursors is selectively removed from said ionized

substances; and

measuring an amount of the negative ions produced.

18. A monitoring apparatus comprising:

a sampling pipe having a sampling port for sampling
5 a gas;

a first filter for removing impurities from said
sampled gas;

an ionizer for ionizing sample gas which has passed
through said filter by a discharge;

10 a second filter for removing microparticles from
ionized substances;

a mass spectrometer which dissociates a chlorine atom
from the ionized substances which have passed through said
second filter; and

15 an ion/charge converter for measuring the current of
the remaining ions.

19. An incinerator comprising:

a garbage hopper;

a furnace for burning said garbage;

20 a gas supply nozzle for supplying gas to the interior
of said furnace;

a boiler for recovering heat from said incinerator;

a flue for discharging flue gas which has passed
through said boiler;

25 a sampling port for sampling flue gas from either or

both of said gas supply nozzle or said boiler;

an ion source for ionizing gas from said sampling port
by a discharge;

a measuring device for measuring a predetermined
5 target substance contained in said flue gas from the ionized
substance from said ion source; and

a controller for controlling the temperature of said
incinerator by the measured results.

20. An incinerator comprising:

10 a garbage hopper;

a furnace for burning said garbage;

a gas supply nozzle for supplying gas to the interior
of said furnace;

a boiler for recovering heat from said incinerator and
15 a flue for discharging flue gas which has passed through said
boiler;

a sampling port for sampling flue gas from either or
both of said gas supply nozzle or said boiler;

an ion source for ionizing gas from said sampling port
20 by a discharge;

a measuring apparatus for measuring a predetermined
target substance contained in said flue gas from the ionized
substance from said ion source; and

a display device for displaying flue gas sampling
25 points of said incinerator, displaying measured results at said

sampling points, and outputting an alarm when said results exceed predetermined values.

5

10

15

20

25